



STARK INDUSTRIAL
527 DUNDONALD STREET, FREDERICTON, NB, E3B 1X5
CANADA 1-888-709-7773

PRODUCT: WGL



Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

SUPPLIER STARK INDUSTRIAL
527 DUNDONALD STREET, FREDERICTON
ONTARIO
CANADA
E3B 1X5

PRODUCT NAME..... WGL
CHEMICAL FAMILY..... GREASE.
MOLECULAR WEIGHT..... NOT APPLICABLE.
CHEMICAL FORMULA..... MIXTURE.
TRADE NAMES & SYNONYMS..... WGL
PRODUCT USES..... GREASE.
FORMULA/LAB BOOK #..... N/A

Section 02: COMPOSITION/INFORMATION INGREDIENTS

Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
HEPTANE	5-10	400 ppm	142-82-5	>15000 mg/kg ORAL-RAT	NOT AVAILABLE
MINERAL SPIRITS	1-5	100 ppm	64742-47-8	>5000 mg/kg ORAL - RAT	1400 ppm/4H INHAL - RAT
ISOBUTANE	1-5	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	5-10	1000 ppm	74-98-6	>5000 mg/kg DERMAL-RABBITS	NOT AVAILABLE

Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:
INGESTION..... MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS.
INHALATION..... INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE ASPHYXANT.
EYE CONTACT..... VAPORS MAY IRRITATE.
SKIN ABSORPTION..... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.
SKIN CONTACT..... MAY CAUSE IRRITATION.
EFFECTS OF ACUTE EXPOSURE..... DIZZINESS, NAUSEA. IRRITATION TO SKIN & EYES.
EFFECTS OF CHRONIC EXPOSURE..... SOLVENTS MAY CAUSE DEFATTING DERMATITIS

Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR. IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... >225.
SPECIAL PROCEDURES..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARATUS SHOULD BE WORN IN A FIRE INVOLVING THIS MATERIAL.
FLAMMABILITY..... CAUTION-FLAMMABLE.
IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
EXTINGUISHING MEDIA..... WATER, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
UPPER FLAMMABLE LIMIT..... 9.4.
(% BY VOLUME)
LOWER FLAMMABLE LIMIT..... 1.
(% BY VOLUME)
EXPLOSION DATA
SENSITIVITY TO STATIC DISCHARGE..... NOT APPLICABLE.
SENSITIVITY TO IMPACT..... NOT APPLICABLE.
HAZARDOUS COMBUSTION PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
AEROSOL FLAME PROJECTION
CLASSIFIED AS:..... >45cm BUT <100cm.
FLASHBACK..... NONE.
FLASH POINT(°C),TAG CLOSED-CUP LOWEST KNOWN VALUE IS HEPTANE @ -7°C.
(CONCENTRATE)

PRODUCT: WGL**Section 06: ACCIDENTAL RELEASE MEASURES**

LEAK/SPILL..... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE.

Section 07: HANDLING AND STORAGE

STORAGE NEEDS..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES.
 ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS).
 HANDLING PROCEDURES AND EQUIPMENT..... STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C.
 SYNERGISTIC MATERIALS..... NONE KNOWN.

Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

GLOVES/ TYPE..... WEAR CHEMICAL RESISTANT GLOVES.
 RESPIRATORY/TYPE..... IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED.
 EYE/TYPE..... SAFETY GLASSES.
 FOOTWEAR/TYPE..... NOT NORMALLY REQUIRED.
 OTHER/TYPE..... NOT REQUIRED.

Section 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... AEROSOL.
 APPEARANCE..... BEIGE.
 ODOR..... HYDROCARBON.
 ODOR THRESHOLD..... NOT AVAILABLE.
 VAPOUR PRESSURE(PSIG)-AEROSOL..... 55-65.
 @ 20 C
 BOILING POINT (°C)(CONC)..... 92 °C BASED ON HEPTANE.
 EVAPORATION RATE..... LESS THAN 1.
 n-BUTYL ACETATE = 1
 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1.
 SOLUBILITY IN WATER g/L (20°C)..... MISCIBLE.
 pH..... NOT AVAILABLE.
 SPECIFIC GRAVITY (LIQUID)..... 0.92-0.94.
 COEFFICIENT OF WATER/OIL DIST..... NOT AVAILABLE.
 FREEZING POINT: (°C)..... NOT AVAILABLE.
 AEROSOL PERCENT VOLATILE..... 26-27.
 (BY WEIGHT).
 SPECIFIC GRAVITY (AEROSOL)..... 0.83-0.86.

Section 10: STABILITY AND REACTIVITY

HAZARDOUS PRODUCTS OF DECOMPOSITION..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE.
 CHEMICAL STABILITY:
 YES..... UNDER NORMAL CONDITIONS.
 NO, WHICH CONDITIONS?..... NOT APPLICABLE.
 COMPATIBILITY WITH OTHER SUBSTANCES:
 NO, WHICH ONES?..... STRONG OXIDIZING AGENTS.
 REACTIVITY CONDITIONS?..... NOT APPLICABLE.
 HAZARDOUS POLYMERIZATION..... WILL NOT OCCUR.

Section 11: TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS..... BENZENE - CAUSES FOETOTOXICITY IN ANIMALS AT DOSES WHICH ARE MATERNALLY TOXIC. DOES NOT IMPAIR FERTILITY.
 IRRITANCY OF MATERIAL..... SKIN/EYE IRRITANT.
 SENSITIZING CAPABILITY OF MATERIAL..... UNKNOWN.
 CARCINOGENICITY OF MATERIAL..... HEPTANE CONTAINS TRACE AMOUNT OF BENZENE - CARCINOGENIC RISKS TO HUMANS BASED ON THE EVALUATION OF IARC WORKING GROUP.
 TERATOGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE ANTICIPATED.
 MUTAGENICITY..... NO INFORMATION IS AVAILABLE AND NO ADVERSE MUTAGENIC EFFECTS ARE ANTICIPATED.

Section 12: ECOLOGICAL CONSIDERATIONS

ENVIRONMENTAL..... NOT AVAILABLE.

Section 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL..... DO NOT PUNCTURE OR INCINERATE CONTAINERS, EVEN WHEN EMPTY. DISPOSE OF IN ACCORDANCE WITH LOCAL, PROVINCIAL AND FEDERAL REGULATIONS.

PRODUCT: WGL**Section 14: TRANSPORTATION INFORMATION**

T.D.G. CLASSIFICATION..... CONSUMER COMMODITY(AEROSOLS, UN1950, CLASS 2.1) .
D.O.T. CLASSIFICATION..... CONSUMER COMMODITY, ORM-D.

Section 15: REGULATORY INFORMATION**CANADIAN REGULATIONS:**

WHMIS CLASSIFICATION..... A,B5,D2B.
CNFC SECTION 3.3.5..... LEVEL 1.
CEPA (Canadian Environmental Protection Act) ALL SUBSTANCES IN THIS PRODUCT ARE LISTED ON THE CANADIAN DOMESTIC
SUBSTANCES LIST (DSL) OR ARE NOT REQUIRED TO BE LISTED.

U.S. REGULATIONS:

HMIS RATING HEALTH..... 2 MODERATE HAZARD.
HMIS RATING FLAMMABILITY..... 4 SEVERE HAZARD.
HMIS RATING REACTIVITY..... 0 MINIMAL HAZARD.
HMIS RATING PERSONAL PROTECTION..... B.
NFPA CODE 30B..... LEVEL 1.
SARA 313 INFORMATION: THIS PRODUCT CONTAINS NO INGREDIENTS SUBJECT TO THE REPORTING REQUIREMENTS
OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF
1986 AND OF 40 CFR 372.
CAS #: CHEMICAL NAME:
N/A.
CALIFORNIA PROPOSITION 65: THE FOLLOWING STATEMENT IS MADE IN ORDER TO COMPLY WITH THE CALIFORNIA SAFE
DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986:
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA
TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.
CAS #: CHEMICAL NAME:
*71-43-2 BENZENE (TRACE AMOUNT IN HEPTANE)
TSCA (Toxic Substances Control Act)..... ALL COMPONENT OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY. ANY
IMPURITIES PRESENT IN THIS PRODUCT ARE EXEMPT FROM LISTING.
VOC (w/w%)..... 26-27.

Section 16: OTHER INFORMATION

NOTICE FROM STARK INDUSTRIAL..... THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY STARK
INDUSTRIAL FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR
USE BY SKILLED PERSONS AT THEIR OWN RISK. STARK INDUSTRIAL ASSUMES NO
RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE.
THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE
SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN
COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.
PREPARED BY..... STARK INDUSTRIAL
PREPARATION DATE Nov 11, 2016

