



SAFETY DATA SHEET

1. Identification

Product identifier STAINLESS BRITE

Other means of identification n/a

Product code

Recommended use CLEANER/POLISH

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name STARK INDUSTRIALS
Address 527 Dundonald Street
Fredericton, New Brunswick E3B 1X5
Canada
Telephone General Assistance 1-888-709-7773
Emergency phone number 1-888-709-7773

Supplier Not available.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity (fertility)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

Hazardous to the aquatic environment,
long-term hazard

Category 3

Other hazards

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha (petroleum), Hydrotreated Heavy		64742-48-9	40.841
Propane		74-98-6	18.603
Isobutane		75-28-5	8.397
Heptane, branched, cyclic and linear		426260-76-6	5.319
Naphtha (petroleum), Hydrotreated Light		64742-49-0	5.317
Isopropyl Alcohol		67-63-0	4.62
Cyclohexane		110-82-7	1.813
n-Hexane		110-54-3	0.181
Octane		111-65-9	0.181

Other components below reportable levels

14.727

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
Environmental precautions	<p>Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.</p> <p>Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.</p>

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	<p>Level 3 Aerosol.</p> <p>Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).</p>

8. Exposure controls/personal protection

Occupational exposure limits			
US. ACGIH Threshold Limit Values			
Components	Type	Value	
Cyclohexane (CAS 110-82-7)	TWA	100	ppm
Isobutane (CAS 75-28-5)	STEL	1000	ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400	ppm
	TWA	200	ppm
n-Hexane (CAS 110-54-3)	TWA	50	ppm
Octane (CAS 111-65-9)	TWA	300	ppm
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)			
Components	Type	Value	
Cyclohexane (CAS 110-82-7)	TWA	344 mg/m3	
			100 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	984 mg/m3	
			400 ppm
	TWA	492 mg/m3	
			200 ppm
n-Hexane (CAS 110-54-3)	TWA	176 mg/m3	
			50 ppm
Octane (CAS 111-65-9)	TWA	1400 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Propane (CAS 74-98-6)	TWA	1000 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	20 ppm
Octane (CAS 111-65-9)	TWA	300 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
Octane (CAS 111-65-9)	TWA	300 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Isobutane (CAS 75-28-5)	TWA	800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	1030 mg/m3
		300 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1230 mg/m3
		500 ppm
	TWA	983 mg/m3
		400 ppm
n-Hexane (CAS 110-54-3)	TWA	176 mg/m3
		50 ppm
Octane (CAS 111-65-9)	STEL	1750 mg/m3
		375 ppm
	TWA	1400 mg/m3
		300 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

ACGIH Biological Exposure Indices Components		Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)		0.4 mg/l	2,5-Hexanedione, without hydrolysis	Urine	*
* - For sampling details, please see the source document.					
Exposure guidelines					
Canada - Alberta OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Canada - British Columbia OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Canada - Manitoba OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Canada - Ontario OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Canada - Quebec OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Canada - Saskatchewan OELs: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
US ACGIH Threshold Limit Values: Skin designation					
n-Hexane (CAS 110-54-3)			Can be absorbed through the skin.		
Appropriate engineering controls		Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.			
Individual protection measures, such as personal protective equipment					
Eye/face protection		Chemical respirator with organic vapor cartridge and full facepiece.			
Skin protection					
Hand protection		Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.			
Other		Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.			
Respiratory protection		Chemical respirator with organic vapor cartridge and full facepiece.			
Thermal hazards		Wear appropriate thermal protective clothing, when necessary.			
General hygiene considerations		Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.			
9. Physical and chemical properties					
Appearance					
Physical state		Liquid.			
Form		Aerosol.			
Color		Not available.			
Odor		Not available.			
Odor threshold		Not available.			
pH		Not available.			
Melting point/freezing point		Not available.			
Initial boiling point and boiling range		177.26 °F (80.7 °C) estimated			
Flash point		-156.0 °F (-104.4 °C) PROPELLANT estimated			
Evaporation rate		Not available.			
Flammability (solid, gas)		Not applicable.			

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.4 % estimated

Flammability limit - upper (%) 9.6 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 139.06 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 32880 mg/m3, 4 Hours > 5540 ppm, 4 Hours
Oral		
LD50	Rabbit	> 5000 mg/kg

Components	Species	Test Results
Isobutane (CAS 75-28-5)	Rat	> 5000 mg/kg
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	> 10000 ppm, 6 Hours
Oral		
LD50	Rat	5.84 g/kg
Naphtha (petroleum), Hydrotreated Heavy (CAS 64742-48-9)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
Naphtha (petroleum), Hydrotreated Light (CAS 64742-49-0)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig; Rabbit Rabbit	> 9.4 ml/kg, 24 Hours > 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours > 4980 mg/m3 > 4980 mg/m3, 4 Hours > 4.96 mg/l, 4 Hours 13700 ppm, 4 Hours
Oral		
LD50	Rat	4820 mg/kg
n-Hexane (CAS 110-54-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
Inhalation		
LC50	Rat	> 5000 ppm, 24 Hours > 31.86 mg/l 73860 ppm, 4 Hours

Components	Species	Test Results
Oral		
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
Octane (CAS 111-65-9)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 24.88 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Canada - Alberta OELs: Irritant	
Octane (CAS 111-65-9)	Irritant
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	
ACGIH Carcinogens	
Isopropyl Alcohol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.
Canada - Manitoba OELs: carcinogenicity	
2-PROPANOL (CAS 67-63-0)	Not classifiable as a human carcinogen.
Reproductive toxicity	Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.	
Components	Species	Test Results
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours

Components	Species		Test Results
Isopropyl Alcohol (CAS 67-63-0)			
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
n-Hexane (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
* Estimates for product may be based on additional component data not shown.			
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Partition coefficient n-octanol / water (log Kow)			
Cyclohexane			3.44
Isobutane			2.76
Isopropyl Alcohol			0.05
n-Hexane			3.9
Octane			5.18
Propane			2.36
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal considerations			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.		
14. Transport information			
TDG			
UN number	UN1950		
UN proper shipping name	AEROSOLS, flammable		
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Packing group	Not applicable.		
Environmental hazards	Yes		
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.		
IATA			
UN number	UN1950		
UN proper shipping name	Aerosols, flammable		
Transport hazard class(es)			
Class	2.1		
Subsidiary risk	-		
Label(s)	2.1		
Packing group	Not applicable.		
Environmental hazards	Yes		

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG; TDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date 06-23-2017

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.